



Art.-No.: YWDLA-RADT-1801
LED luminaire "LARIO", w-/c- surface mounting, round,
300x58mm, 18W, 2150lm, 3000, 4000, 6000K, Dip-Switch,
CRI >80, IP54, white, Triac



LED ceiling- and wall-mounted luminaire, LARIO series, IP54. Housing and diffuser made from PC (fire- and UV-resistant), opal. Operating unit integrated (can be switched). Three-stage adjustment of colour temperature (3000K, 4000K, 5700K) using DIP switch. Version with CASAMBI Bluetooth control available.

TECHNICAL DATA

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0.9
System power	18 W
Dimming	TRIAC
Electrical version	with internal operating device, dimmable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	3000/4000/6000 K
Rated luminous flux	2,150 lm
Luminous efficacy	119 lm/W
Light colour	830/840/860
Colour tolerance	3
Beam angle	113 °
UGR	23.9
Lifetime (h, at 25°C)	50,000 h, L80
Acceptance tests	
Certifications	CE, ROHS
Protection class	II
Ingress protection (IP) rating	IP 54
Ambient temperature	-20 to +45 C°



Physical data	
Mounting method	ceiling mounted, wall mounted
Housing material	PC
Housing colour	white
Cover material	PC
Height (H)	58 mm
Diameter \varnothing	300 mm
Product weight	0.76 kg
Weight incl. Packaging	1.05 kg



LIGHT DISTRIBUTION

