



Art.-No.: YWDZO-LAWS-6101-D
LED lamp "ZORRO", wall / ceiling surface mounting,
1590x165x63mm, 61W, 5900lm 3000K, CRI >80, IP40,
switchable



LED ceiling- and wall-mounted luminaire, ZORRO. Housing made from steel plate, white, powder-coated. Diffuser made from plastic (PC), opal, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. Version with CASAMBI® Bluetooth control available. DC compatible. NANO protection on request.

TECHNICAL DATA

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0.9
System power	61 W
Inrush current	35 A
Inrush current duration	240 µs
Luminaires on C16A fuse	26 Stk.
Connection cross section	2.5 mm ²
Electrical version	with internal operating device, switchable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	3,000 K
Rated luminous flux	5,900 lm
Luminous efficacy	97 lm/W
Light colour	830
Colour rendering index (CRI)	> 80
Colour tolerance	3
Beam angle	90 °
UGR	26.1
Lifetime (h, at 25°C)	75,000 h, L80



Acceptance tests	
Certifications	CE
Protection class	I
Ingress protection (IP) rating	IP 40
Ambient temperature	-20 to +25 C°
Physical data	
Mounting method	ceiling mounted
Housing material	Steel sheet
Housing colour	white
Cover material	PC
Length (L)	1,590 mm
Width (B)	165 mm
Height (H)	63 mm
Product weight	3 kg
Weight incl. Packaging	3.5 g
Packaging Length (L)	1,612 mm
Packaging Width (B)	166 mm
Packaging Height (H)	57 mm



LIGHT DISTRIBUTION

